

QL-120Xe

Tabletop Color Label Printer

Full-Featured Performance, Cost Effective Labels



The QL-120Xe is a cost-effective, in-house color labeling solution that delivers high performance and reliability allowing businesses to achieve attractive and compelling branding for their products.

The QL-120Xe provides an economical way to start producing custom color labels with potential savings for months or years to come.

Featuring a native 1200 x 1200 dpi, extended life printhead matched with QuickLabel's proprietary dye ink formulation, the QL-120Xe is ready to deliver true-to-life color images unmatched by any other digital labeling system in its class.

- Full-featured performance, friendly price
- Vibrant color labels with exceptional 1200 dpi print resolution
- Print widths from 0.5" to 4.2"
- Excellent reliability, world-class support

Technical Specifications

Operation

Ink Type	Dye ink, (4) individual CMYK cartridges
Print Resolution	1200 x 1200 dpi / 1200 x 600 dpi
Print Speed	2 ips (50 mm/sec) - 12 ips (305 mm/sec)
Print Area*	Width: 0.5" (12.7 mm) - 4.17" max (105.9 mm) Length: 0.24" (6 mm) - 30" (762 mm)
Media Sensors	Gap, Reflective (black mark), Continuous
Cutter	Automatic, guillotine-type, cut at end of batch or between labels, 1.0" (25 mm) minimum cut length rated for 1.5M cuts on 1.8 mil, 65g/m2 paper liner
Connectivity	High-speed USB 2.0; Gigabit ethernet RS-232 external control interface and protocol
Software	Microsoft Windows® 10, 8.1, 8, 7; Windows Server® 2019, 2016, 2012, 2008, 64/32-bit drivers, CQL Pro advanced label creation and print management software (one free license included), Nicelabel® enterprise or desktop software (optional)

Environmental & Physical

Printer Operating	59° F to 86° F (15° C to 30° C), 10% to 90% Relative Humidity (non-condensing)
Power Requirements	100 - 240 VAC 50/60Hz, 1.5A/0.5A
Power Consumption	268W (max)
Noise Level	Less than 60dB while printing, less than 40dB during standby (ISO7779)
Dimensions	15.2" L x 22.2" W x 15.5" H (286 mm x 564 mm x 394 mm)
Weight	52.9 lbs. (24 kg) without supplies 56.1 lbs. (26 kg) with supplies 68.2 lbs. (31 kg) shipping
Optional Accessories	RW-5.1 Automatic Label Roll Rewinder, 11.8" (300 mm) OD Roll UW-5.1 Automatic Label Roll Unwinder, 11.8" (300 mm) OD Roll External Control Interface

* Consult with our media sales specialists for label widths narrower than 0.75" (19mm)

** Construction = print width + edge trim

Supplies

Ink Cartridges	QL-120Xe CMYK dye cartridges, 240 mL, (230 mL usable)
Maintenance Cartridge	450 mL full replacement; 360 mL (80%) near full warning

Labels and Tags

Construction**	Width: 1.0" (25.4 mm) - 4.53" (115 mm) Length: 0.24" (6 mm) - 30" (762 mm)
Thickness	5.7 mil (0.145 mm) – 10 mil (0.255 mm)
Roll Size	8" OD (200 mm), 3" ID (76 mm) core 11.8" OD (300 mm) with optional UW-5.1 External Unwind
Types	Matte, semi-gloss, high gloss papers, and synthetics as well as tag stocks and other specialty labels

Warranty

One-Year Astronova Product Identification Standard Limited Warranty (excludes wear parts and supplies)



The Labels You Want When You Need Them.



Authorised Distributor in India

ONYX EQUIPMENTS (INDIA) PVT. LTD.

107, Supreme HQ, Bangalore Highway, Baner, Pune - 411 045, INDIA.

T : +91 8237006614 E : salespune@onyxindia.in W : onyxindia.in

ASTRONOVA INC,
600 East Greenwich Avenue,
West Warwick, 02893 Rhode Island,
USA T : +1 401-828-4000